

Brand	Lexar [®]		
Product Name Full	Lexar® Professional 1066x SDXC™ UHS-I Card SILVER Series		
Product Name Short	Professional 1066x SDXC™ UHS-I Card SILVER Series		
Product Line	Professional		
Marketing Text Long 25-Word Description (<750characters)	The Lexar® Professional 1066x SDXC™ UHS-I Card SILVER Series lets you quickly capture and transfer files, including Full-HD and 4K UHD video with speeds up to 160MB/s read, and up to 120MB/s write¹.		
Marketing Text 50-Word Description (<750characters) Bullet Feature 1	Design for your DSLR or mirrorless camera, the Lexar ® Professional 1066x SDXC™ UHS-I Card SILVER Series lets you quickly capture and transfer high-quality photos, including Full- HD and 4K UHD video with speeds up to 160MB/s read, and up to 120MB/s write¹. These cards dramatically accelerate workflow from start to finish maximizing your creativity. High-speed performance – rated UHS Speed Class 3 (U3) and Video Speed Class 30		
Bullet Frateur 0	(V30) for your DSLR or mirrorless camera Leverages LHS-L technology to deliver read speeds up to 160MB/s1		
Bullet Feature 2	Leverages UHS-I technology to deliver read speeds up to 160MB/s ¹ Quickly capture high-quality images and extended lengths of Full-HD and 4K UHD with write		
Bullet Feature 3	speeds up to 120MB/s		
Bullet Feature 4	High-capacity options – up to 1TB		
Bullet Feature 5	Design for durability in harsh conditions ²		
Bullet Feature 6	Includes Lexar Recovery Tool to recover most photo and select video files ³		
Footnote(s)/ Disclaimer(s)	[¹North America (NA) version:] ¹Up to 160MB/s read transfer, write speeds lower. Engineered with advanced technology to reach read/write speed beyond UHS-I 104MB/s specification. Speeds based on internal testing. Actual performance may vary. Read/write speed full performance achieved only when paired with Lexar Reader. For more information, please contact Lexar Technical Support. [¹GL/CN/JP version:] ¹Up to 160MB/s read transfer, write speeds lower. Engineered with advanced technology to reach read/write speed beyond UHS-I 104MB/s specification. Speeds based on internal testing. Actual performance may vary. Read/write speed full performance achieved only when paired with Lexar Reader. For more information, please contact Lexar Technical Support. [²ALL Regions:]		



	² Waterproof: Protection against water.
	Temperature-proof: Withstands operating temperature range from 32°F (0°C) or 158°F (70 °C)
	and non- operating temperatures from -13°F (-25°C) or 185°F (85 °C).
	Shockproof : Shock resistant (200G [1961.33m/sec^2] 3ms, 150G [1471.00m/sec^2] 10ms,
	From X.Y.Z, 3 directions/3 times each)
	Vibration proof: Vibration resistant (10Hz to 2000 Hz, 6Grms, 5 minutes per 1 cycle, 10 cycle per
	1 axis total 30 cycles per 3 axis, based on IEC 60512-6-4 guidelines).
	X-ray-proof: Protected against X-ray exposure based on ISO7816-1 guidelines.
	³ Image or other data recovery is not 100%
	guaranteed. Based on internal testing. Actual
	performance may vary. Lexar is not liable for any
	loss of data or images.
	[Note:]
	[Product page only:] Product appearance, performance, software offerings, and packaging may vary
	depending on ship date and available inventory. Actual usable memory capacity may vary. 1GB equals 1 billion bytes.
	<u>Limited lifetime warranty for card and one-year limited warranty for adapter (Americas only)</u>
Warranty	10-year limited warranty for card and one-year limited warranty for adapter (Outside of
	the Americas)
Market Segment	Electronics, Computers & accessories, cameras & photo, video
Category	Memory Cards, Camera, Photo, Video, Digital camera accessories, Video camera accessories, DSLR
Sub Category	SDXC, Lexar, High-Speed, 1066x, Class 10, UHS-I, 64GB, 128GB. 256GB, 512GB, 1TB
	SDXC UHS-I:
	sdxc memory card, sdxc, sdxc card, sd, SD cards, sdhc flash memory, memory cards,
	flash card, SDHC memory, video memory card, secure digital cards, memory cards digital
Keywords for Search	camera, digital camera cards, lexar professional, UHS-I,UHS-II, HD video, 4K Video, high-speed, Class 10, 1066x, DSLR, 64GB, 128GB, 256GB, 512GB, 1TB, U3 SD card, V30
	SD
	card

Setup Sheet Lexar® Professional 1066x SDXC™ UHS-I Card SILVER Series



Specifications		
Module Type/ Form Factor	SDXC UHS-I	
Capacities and Speed	SDXC: 64GB – Class 10, U3, V30, 1066x (up to 160MB/s read, up to 70MB/s write¹) 128GB – 1TB – Class 10, U3, V30 1066x (up to 160MB/s read, up to 120MB/s write¹)	
Operating Temperature	0° C to 70° C (32°F to 158°F)	
Storage Temperature	-25° C to 85° C (-13°F to 185°F)	
Shock	N/A	
Vibration	N/A	
Humidity	N/A	

		Ordering information		
	Part Number	Description	Single UPC	25 Pack UPC
_	LSD1066064G- BNNNU	Lexar Pro SDXC 1066X 64G NA	843367122370	90843367122373
	LSD1066128G- BNNNU	Lexar Pro SDXC 1066X 128G NA	843367122387	90843367122380
Single UPC and/or Master	Part Number	Description	Single UPC	10 Pack UPC
Carton UPC (NA)	LSD1066256G- BNNNU	Lexar Pro SDXC 1066X 256G NA	843367122394	10843367122391
	LSD1066512G- BNNNU	Lexar Pro SDXC 1066X 512G NA	843367122400	10843367122407
	LSD1066001T- BNNNU	Lexar Pro SDXC 1066X 1TB BL, NA	843367127856	10843367127853
	Part Number	Description	Single UPC	25 Pack UPC
	LSD1066064G- BNNNG	Lexar Pro SDXC 1066X 64G GL	843367122417	90843367122410
	LSD1066128G- BNNNG	Lexar Pro SDXC 1066X 128G GL	843367122424	90843367122427
Single and/or	Part Number	Description	Single UPC	10 Pack UPC
Master Carton UPC (Global)	LSD1066256G- BNNNG	Lexar Pro SDXC 1066X 256G GL	843367122431	10843367122438
	LSD1066512G- BNNNG	Lexar Pro SDXC 1066X 512G GL	843367122448	10843367122445
	LSD1066128G- B2NNG	Lexar Pro SDXC 1066X 128G GL 2 pack	843367126507	10843367126504
	LSD1066001T- BNNNG	Lexar Pro SDXC 1066X 1TB, BL, Global	843367127849	10843367127846
	-			

Setup Sheet

exar [®] Professional 1066	x SDXC™ UHS-	-I Card SILVER Series
-------------------------------------	--------------	-----------------------

Setup Sheet Lexar® Profession	nal 1066x SDXC™ UHS-I	Card SILVER Series		Lexar
	Part Number	Description	Single UPC	xx Pack UPC
	LSD1066064G- RNNNC	Lexar Pro SDXC 1066X 64G CN	843367122455	1084336712245 2
Single and/or Master Carton UPC (CN)	LSD1066128G- RNNNC	Lexar Pro SDXC 1066X 128G CN	843367122462	1084336712246 9
	LSD1066256G- RNNNC	Lexar Pro SDXC 1066X 256G CN	843367122479	1084336712247 6
	LSD1066512G- RNNNC	Lexar Pro SDXC 1066X 512G CN	843367122486	1084336712248 3
Country of Origin	Taiwan			
Harmonized Tariff Schedule	8523.51.0000			
Compliance	CE, FCC,VCCI, C-Tick, WEEE, CNAS			

	Weights and Dimensions	S	
Product			
Unit Weight	0.004 lbs	2.0g	
Unit Dimensions L x W x H	1.25 x 0.95 x 0.08 inches	32 x 24 x 2.1 mm	
Image	1 TB 160 MB/s V30 U EXCIPTORESSIONAL 160 MB/s		
Blister (NL / GLOBAL / C	N)		
Package Type	Single Pack		
Qty Per Package	1		
Shipping Weight	0.031 lbs 14g		
Package Dimensions L x W x H	L 5.500" x W 4.000" x H 0.210"	L139.7 x W 101.6 x H 5.3 mm	
Blister - Master Pack (NA	and Global) 1TB		
Package Type	Master Carton Small Blister Single Pack		
	-		

Setup Sheet Lexar® Professional 1066x SDXC™ UHS-I Card SILVER Series



oxai i i olooolollai i ooox	SDXC '" UHS-I Card SILVER Series	EC.ZGI	
Retail Master Pack Quantity	10		
Shipping Weight	0.36 lbs	163g	
Package Dimensions L x W x H	L 5.91" x W 1.73" x D 4.53"	L 150 x W 44 x H 115mm	
Blister - Master Pack (NA	and Global) 256 / 512GB; (CN) all capacity		
Package Type	Master Carton Small Blister Single Pack		
Retail Master Pack Quantity	10		
Shipping Weight	0.36 lbs	163g	
Package Dimensions _ x W x H	L 5.91" x W 1.73" x D 4.53" L 150 x W 44 x H 115mm		
Blister - Master Pack (NA	and Global) 64 / 128GB		
Package Type	Master Carton Small Blister Single Pack		
Retail Master Pack Quantity	25		
Shipping Weight	0.839 lbs	389g	
Package Dimensions _ x W x H	L 5.91" x W 4.13" x D 4.53" L 150 x W 105 x H 115n		
Blister (Global)			
Package Type	Small Blister 2 Pack		
Retail Master Pack Quantity	Small Blister 2 Pack 1		
Shipping Weight	0.035 lbs 16g		
Package Dimensions _ x W x H	L 5.500" x W 4.000" x H 0.210"	L139.7 x W 101.6 x H 5.3 mm	
Blister – Master Carton (N	IA and Global)		
Package Type	Master Carton Small Blister 2 Pack		
Qty Per Package	10		
Shipping Weight	0.36 lbs	163 g	
Package Dimensions	L 5.91" x W 1.73" x D 4.53"	L 150 x W 44 x H 115mm	