

Brand	Lexar®
Product Name Full	Lexar® High-Performance 800x PRO SDHC™/SDXC™ UHS-I Card BLUE Series
Product Name Short	High-Performance 800x PRO SDHC™/SDXC™ UHS-I Card BLUE Series
Product Line	High-Performance
Marketing Text Long 25-Word Description (<750 characters)	Lexar® High-Performance 800x PRO SDHC™/SDXC™ UHS-I Cards BLUE Series let you easily capture and quickly offload high-quality photos and 4K UHD video ² with transfer speeds of up to 150MB/s ¹ .
Marketing Text 50-Word Description (<750 characters)	Lexar® High-Performance 800x PRO SDHC™/SDXC™ UHS-I Cards BLUE Series are designed for point-and-shoot and mid-range DSLR cameras, and HD camcorders. They feature fast transfer speeds of up to 150MB/s ¹ so you can perfectly capture and quickly transfer high-quality images and 4K UHD video ² .
Bullet Feature 1	Designed with UHS-I technology for point-and-shoot and mid-range DSLR cameras and HD camcorders
Bullet Feature 2	Share your images faster with higher transfer speeds of up to 150MB/s ¹
Bullet Feature 3	Capture high-quality images and stunning 4K UHD video ²
Bullet Feature 4	High-speed performance lets you transfer files from card to computer to dramatically accelerate your workflow
Bullet Feature 5	Designed for durability-temperature, shock, vibration and X-ray proof ³
Footnote(s)/ Disclaimer(s)	<p>¹ Up to 150MB/s read transfer, write speeds lower. Engineered with advanced technology to reach read/write speed beyond UHS-I 104MB/s specification. Speeds based on internal testing. Actual performance may vary. Read/write speed full performance achieved only when paired with Lexar Multi-Card 2-in-1 USB 3.1 Reader or Lexar Professional Multi-Card 3-in-1 USB 3.1 Reader marked with Rev B. For more information, please contact Lexar Technical Support.</p> <p>² 4K UHD video capability based on 64GB, 128GB, and 256GB capacities only.</p> <p>³ Temperature-proof: Withstands operating temperature range from 32°F (0°C) or 158°F (70 °C) and non-operating temperatures from -13°F (-25°C) or 185°F (85 °C).</p> <p>Shock-proof: Shock resistant (200G [1961.33m/sec²] 3ms, 150G [1471.00m/sec²] 10ms, From X.Y.Z, 3 directions/3 times each)</p> <p>Vibration-proof: Vibration resistant (10Hz to 2000 Hz, 6Grms, 5 minutes per 1 cycle, 10 cycle per 1 axis total 30 cycles per 3 axis, based on IEC 60512-6-4 guidelines).</p> <p>X-ray-proof: Protected against X-ray exposure based on ISO7816-1guidelines.</p> <p>Lexar is not liable for any loss of data or images.</p> <p>[Product page only:] Product appearance, performance, software offerings, and packaging may vary depending on ship date and available inventory.</p> <p>Actual usable memory capacity may vary. 1GB equals 1 billion bytes.</p>
Warranty	10-year limited warranty
Market Segment	Consumer Electronics, Camera, Photo, Video
Category	Memory Cards, Camera, Photo, Video, Digital camera accessories, Video camera accessories
Sub Category	SDHC, SDXC, Lexar, High-Speed, 800x PRO, Class 10, UHS-I, Lexar, 32GB, 64GB, 128GB, 256GB

Keywords for Search	<p>SDHC: sdhc memory card, sdhc, sdhc card, sd, SD cards, sdhc flash memory, memory cards, flash card, SDHC memory, video memory card, secure digital cards, memory cards digital camera, digital camera cards,, lexar High-Performance, uhs-I, HD video, high-speed, Class 10, 800x PRO, DSLR, 32GB, U1 SD card, V10 SD card</p> <p>SDXC: sdxc memory card, sdxc, sdxc card, sd, SD cards, sdxc flash memory, memory cards, flash card, SDXC memory, video memory card, secure digital cards, memory cards digital camera, digital camera cards, image rescue, lexar High-Performance, uhs-I, HD video, high-speed, Class 10, 800x PRO, DSLR, 64GB, 128GB, 256GB, U3 SD card, V30 SD card</p>
----------------------------	--

Specifications	
Module Type/ Form Factor	SDHC UHS-I/SDXC UHS-I
Capacities and Speed	<p>SDXC: 128GB-256GB—Class 10, U3, V30 (up to 150MB/s read, up to 45MB/s write) 64GB— Class 10, U3, V30 (up to 150MB/s read)</p> <p>SDHC: 32GB—Class 10, U1, V10 (up to 150MB/s read)</p>
Operating Temperature	0°C to 70°C (32°F to 158°F)
Storage Temperature	-25°C to 85°C (-13°F to 185°F)
Shock	N/A
Vibration	N/A

Ordering Information				
Single and/or Inner Carton UPC (Global)	Part Number	Description	Single UPC	Inner Pack UPC
	LSD0800P032G -BNNNG	Lexar Professional SDHC 32GB 800x PRO, Blister, for Global	843367130122	90843367130125
	LSD0800P064G -BNNNG	Lexar Professional SDXC 64GB 800x PRO, Blister, for GL	843367130139	90843367130132
	LSD0800P128G -BNNNG	Lexar Professional SDXC 128GB 800x PRO, Blister, for GL	843367130146	90843367130149
	LSD0800P256G -BNNNG	Lexar Professional SDXC 256GB 800x PRO, Blister, for GL	843367130153	10843367130150

Single and/or Master Carton UPC (CN)	Part Number	Description	Single UPC	Inner Pack UPC
	LSD0800P032G-BNNNC	Lexar Professional SDHC 32GB 800x PRO BL CN	843367129652	90843367129655
	LSD0800P064G-BNNNC	Lexar Professional SDXC 64GB 800x PRO BL CN	843367129669	90843367129662
	LSD0800P128G-BNNNC	Lexar Professional SDXC 128GB 800x PRO BL CN	843367129676	90843367129679
	LSD0800P256G-BNNNC	Lexar Professional SDXC 256GB 800x PRO BL CN	843367129683	10843367129680

Single and/or Master Carton UPC (NA)	Part Number	Description	Single UPC	Inner Pack UPC (25)
	LSD0800P032G-BNNNU	Lexar Professional SDHC 32GB 800x PRO, for NA	843367133895	90843367133898
	LSD0800P032G-B2NNU	Lexar Professional SDHC 32GB 800x PRO, 2pack, for NA	843367133819	90843367133812
	LSD0800P032G-B3NNU	Lexar Professional SDHC 32GB 800x PRO, 3pack, for NA	843367133932	90843367133935
	LSD0800P064G-BNNNU	Lexar Professional SDXC 64GB 800x PRO, for NA	843367133901	90843367133904
	LSD0800P128G-BNNNU	Lexar Professional SDXC 128GB 800x PRO, for NA	843367133918	90843367133911
	LSD0800P128G-B2NNU	Lexar Professional SDXC 128GB 800x PRO, 2pack, for NA	843367133833	10843367133830
	LSD0800P256G-BNNNU	Lexar Professional SDXC 256GB 800x PRO, for NA	843367133925	10843367133922
	Part Number	Description	Single UPC	Inner Pack UPC (10)
	LSD0800P064G-B2NNU	Lexar Professional SDXC 64GB 800x PRO, 2pack, for NA	843367133826	10843367133823
	LSD0800P128G-B2NNU	Lexar Professional SDXC 128GB 800x PRO, 2pack, for NA	843367133833	10843367133830
	LSD0800P256G-BNNNU	Lexar Professional SDXC 256GB 800x PRO, for NA	843367133925	10843367133922

Country of Origin	Taiwan	
Harmonized Tariff Schedule	8523.51.0000	
Compliance	CE, FCC, WEEE, C-Tick, Recycle, China RoHS, UKCA	
Weights and Dimensions		
Product		
Unit Weight	0.004 lbs	2.0 g
Unit Dimensions L x W x H	1.260" x 0.940" x 0.080"	32mm x 24mm x 2.1mm
Image		
Small Blister (NL, GLOBAL)		
Package Type	Single Pack	
Qty Per Package	1	
Shipping Weight	0.031 lbs	14 g
Package Dimensions L x W x H	5.500" x 4.000" x 0.210"	139.7mm x 101.6mm x 5.3mm



Master Pack (All regions)		
Package Type	Small Blister Single Pack	
Retail Master Pack Quantity	10	
Shipping Weight	0.36 lbs	163 g
Package Dimensions L x W x H	5.91" x 1.73" x 4.53"	150 x 44 x 115mm
Master Pack (All regions)		
Package Type	Small Blister Single Pack	
Retail Master Pack Quantity	25	
Shipping Weight	0.859 lbs	375 g
Package Dimensions L x W x H	5.91" x 4.13" x 4.53"	150 x 105 x 115 mm